# Series 5000

### A range of Brazing End Feed capillary fittings.



#### **Features and Benefits:**

- Available in sizes 15-159mm.
- Suitable for connecting copper tubes in accordance with EN 1057.
- 15-54mm primarily designed for solder applications but, with the exception of Union fittings with copper tails, may also be brazed.
- 66.7-159mm designed for brazing applications only and are not suitable to be jointed using soft soldering technique.
- Manufactured from Copper or Gunmetal thereby being immune to dezincification.

Conex Series 5000 (Silver Brazing)			
Size (mm)	Maximum Working pressure (bar)		
	-20° to 100°C	150°C	200°C
15	35.1	29.8	15.8
18	33.3	28.3	15.0
22	30.6	26.0	13.8
28	23.8	20.3	10.7
35	21.1	17.9	9.5
42	19.3	16.4	8.7
54	16.3	13.9	7.3
66.7	15.4	13.1	6.9
76.1	15.4	13.1	6.9
108	14.2	12.1	6.4
133	10.6	7.7	4.1
159	11.8	8.6	4.6

#### Conex | Bänninger

## Series 5000

#### Brazing End Feed capillary range



5270 From: 15mm 159mm







Fitting Reducer



Elbow

5090

To:

From: 15mm

159mm









From: 15 x 1/2" 54 x 2'























\*Conex Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: technical@ibpgroup.com.

Conex Universal Limited: Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM. Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 520 8778 | Email: salesuk@ibpgroup.co.uk | Website: www.ibpgroup.com